

## ClassicBond Paving Supports

Quickly and easily install a paving or decking system to the roofing surface. The paving supports are placed directly to the membrane without the use of adhesives or fasteners of any sort.

The support consists of a high resistance base which is placed directly on to the waterproofing cap sheet. The paving slabs are then placed directly onto the supports without the use of concrete or adhesives of any sort. The base is fitted with guides which position and anchor perfectly the paving slabs and which at the same time act as expansion joints.

All of the supports are modular and can be stacked so as to achieve the height or thickness of gap underneath the paving desired, and eliminating any unevenness of the roof deck itself. The supports are designed to eliminate cracking and damaging of the waterproofing membrane caused by expansion and contraction of the paving or damage caused by walking on the paving.

### Intended Uses

Support for paving slabs or timber decking joists to create a roof top terrace.

### Precautions

1. No cutting of slabs to be done on the roof surface.
2. Ensure all fitted slabs are stable and do not wobble.
3. No debris on the roof before installation.
4. No debris trapped under the supports.
5. Ensure the slabs used are strong enough to be supported by the corners.



### Features and Benefits

- Circular pad Ø145mm with a 15mm lift.
- Fully interlocking when stacking allowing for a range of heights, steps or slopes to leave a level surface.
- Bases fitted with guides which position and anchor the slabs or decking rafters. These guides allow drainage gap for the slabs and allow for expansion between sections.

### Application\*

- 1 Install the ClassicBond roof and details as per specification.
2. Sweep the roof surface to remove any and all debris.
3. Lay the slabs so that each disc supports the corners of 4 slabs. Where they abut walls or steps the support disc are easily divided into halves or quarters.
4. All cut edges of slabs should be at edges that abut upstands.

### ClassicBond Anti-Back Roof Drain

#### Typical Properties & Characteristics\*

<b>Material</b>	HDPE
<b>Colour</b>	Black
<b>Support Diameter</b>	145mm
<b>Support Height</b>	15mm