

### Lap Sealant



#### General:

DuoPly Lap Sealant is used in conjunction with EPDM roofing system. Primarily used for sealing exposed edges of EPDM membrane splices and sealing edges to perimeter walls.

Lap Sealants are extremely durable and their cured rubber consistency enables them to expand and contract with the EPDM membrane.

#### Features & Benefits

- Cured rubber consistency
- Able to expand and contract with the EPDM membrane
- Mastic gun application
- Coverage up to 6.7 linear metres per tube

#### Installation

1. All surfaces must be free of moisture, oil, dirt and other contaminants.
2. After seams are completed with proper splicing material apply a 8mm bead along the exposed edge of the membrane. Where sealing to a wall fill the chase with lap sealant and feather off the exposed bead.

#### Precautions

1. Review the applicable Material Safety Data Sheet for complete safety information prior to use.
2. Lap Sealant is flammable. It contains solvents that are dangerous fire and explosion hazards when exposed to heat, flame or sparks. Store away from all sources of heat, flame or sparks. Do not smoke when applying. Do not use in a confined or unventilated area. Vapors are heavier than air and may travel along ground to a distant ignition source and flash back.
3. If swallowed, do not induce vomiting. Contact a doctor immediately.
4. Avoid contact with eyes. Safety glasses or goggles are recommended. If splashed in eyes, immediately flush eyes with water for at least 15 minutes. Contact a doctor immediately.
5. Avoid contact with skin. Wash your hands thoroughly after handling. In case of contact with skin, thoroughly wash affected area with soap and water.
6. Job site storage temperatures in excess of 32°C may affect shelf life.

Colour	Black
Solids	65%
Flash Point	4°C
Sevice Temp.	-51°C to 82°C
Coverage	6.7 l/m per tube

All the information in this data sheet is based on practical experience and is published in good faith. However, because we have no control over the manner or conditions in which our products are used, or over work undertaken or end product manufactured by the purchaser, we cannot accept liability for results. Responsibility for ascertaining the suitability of products for their purposes rests with the purchaser. All conditions, representations, statements, warranties or guarantees whatsoever, wheter express, implied or statutory, in respect of any goods manufactured, sold or supplied by us are hereby expressly excluded and we accept no liability in respect of any claim for damage or consequential loss caused to any property arising directly or indirectly out of the use of our products or goods.